

P10600V101I_T30

10.1 Inches, 1024xRGBx600, 65K Colors, UnicView LCM



Display

Item	Parameter	Description
Color	65K (65536) colors	16 bit color 5R6G5B
Visual Angle L/R/U/D	70° /70° /50° /60°	
Resolution	1024*600	90° rotated display (600*1024)
Backlight /Lifecycle/Brightness	LED/20,000 HOURS/ 500 cd/m ²	
Working Temperature/ Storage Temperature	-20~+70℃/-30~+80℃	

Voltage & Current

Item	Conditions	Min	Typ	Max	Unit
Power Voltage	-	6	12	35	V
Operation Current	VIN = 12V, Backlight on	-	400	-	mA
	VIN = 12V, Backlight off	-	80	-	mA

Note: Short-circuit J25 to choose Power Input as 5V (4.5V~5.5V)

Interface

Item	Conditions	Min	Typ	Max	Unit
Baudrate	Standard	1200	115200	892900	bps
Interface	RS-232C				
Data Format	1 byte for initial, 8 bytes for data, invalid bytes for checksum, 1 byte for end				
Socket	SMD2.0-8P with lock catch				

Peripherals

No.	Parameter	Description	
1	Touch Screen	4-wire resistance touch screen: P10600V101I_T30	
		4-wire capacitive touch screen: P10600V101I_P30	
		No touch screen: P10600V101I_N30	
2	Buzzer	YES	
3	RTC	YES	
4	USB	YES. For downloading offline or user data copy.	External board needed for online debugging
5	USB Mini	YES. For online debugging.	
6	Audio	Support *.MP3 files. Theoretically 4096 file at maximum. Speaker power: 4Ω 2W or 8Ω 2W.	
7	Keyboard	Support external row keyboard (8*8 maximum).	
8	Memory	128M(support *.jpg files, maximum 65536 files theoretically), extended to 1G at maximum.	



