

P10600V101I_T39

10.1 Inches, 1024xRGBx600, 65K Colors, UnicView LCM



● Display

| Item | Parameter | Description |
|--|--|--------------------------------|
| Color | 65K (65536) colors | 16 bit color 5R6G5B |
| Visual Angle L/R/U/D | 70° /70° /50° /60° | |
| Resolution | 1024*600 | 90° rotated display (600*1024) |
| Backlight /Lifecycle/Brightness | LED/20,000 HOURS/ 1000 cd/m ² | |
| Working Temperature/ Storage Temperature | -20~+70°C/-30~+80°C | |

● Voltage & Current

| Item | Conditions | Min | Typ | Max | Unit |
|-------------------|--------------------------|-----|-----|-----|------|
| Power Voltage | - | 6 | 12 | 35 | V |
| Operation Current | VIN = 12V, Backlight on | - | 590 | - | mA |
| | VIN = 12V, Backlight off | - | 80 | - | mA |

● Interface

| Item | Conditions | Min | Typ | Max | Unit |
|-------------|--|------|--------|--------|------|
| Baudrate | Standard | 1200 | 115200 | 892900 | bps |
| Interface | RS-232C | | | | |
| Data Format | 1 byte for initial, 8 bytes for data, invalid bytes for checksum, 1 byte for end | | | | |
| Socket | SMD2.0-8P with lock catch | | | | |

● Peripherals

| No. | Parameter | Description |
|-----|--------------|---|
| 1 | Touch Screen | 4-wire resistance touch screen: P10600V101I_T39 |
| | | No touch screen: P10600V101I_N39 |
| 2 | Buzzer | YES |
| 3 | RTC | YES |
| 4 | USB | YES. For downloading offline or user data copy. |
| 5 | USB Mini | YES. For online debugging. |
| | | External board needed for online debugging |
| 6 | Audio | Support *.MP3 files. Theoretically 4096 file at maximum. Speaker power: 4 Ω 2W or 8 Ω 2W. |
| 7 | Keyboard | Support external row keyboard (8*8 maximum). |
| 8 | Memory | 128M(support *.jpg files, maximum 65536 files theoretically), extended to 1G at maximum. |



