


P10768MS150C_T01

15.0 Inches, 1024xRGBx768, 16.7M Colors, Android LCM




P10768MS150C_T01 is an industrial level Android LCM based on Rockchip RK3128 ARM. It is equipped with Quad-core Cortex-A17, supports most decoding solutions under 1080p@60fps, H.265/H.264/MVC/VP8 solutions under 1080p@60fps and many other great features of Rockchip RK3128. Meanwhile, with good jpeg picture processing performance and 3D GPU, it supports OpenGL ES2.0 and 1.1 OpenVG1.1.

RK3128 has high-performance external memory interface (DDR3/DDR3L/LPDDR2) capable of sustaining demanding memory bandwidths, also provides a complete set of peripheral interface to support very flexible applications.

Core Board						
CPU	1.2GHz Quad-core A7 ARM					
RAM	1GB DDR3					
eMMC	8GB					
GPU	Mali-T764 MP4					
Power Management	ACT8846 PMU					
System Version						
Android	Android 5.1/7.1					
Ubuntu	Ubuntu 13.09 (Default system is Android. Need to refresh firmware to choose Ubuntu. Apps need to be developed separately.)					
Display						
Color	16.7M (16777216) colors, 24-bit color 8R8G8B.					
Active Area (A.A.)	304.10 mm(W)×228.10 mm(H), 1024×768.					
View Area (V.A.)	307.40 mm(W)×231.30mm(H), 1024×768.					
Resolution	1024×768					
Backlight	LED					
Brightness	300nit					
Optical Specifications						
Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Viewing Angle (CR≥10)	θL	Φ=180° (9 o’ clock)	85	89	—	Degree
	θR	Φ=0° (3 o’ clock)	85	89	—	
	θT	Φ=90° (12 o’ clock)	85	89	—	
	θB	Φ=270° (6 o’ clock)	85	89	—	
Voltage & Current						
Item	Condition		Min.	Typ.	Max.	Unit
Power Voltage			6	12	18	V
Operation Current	—		—	400	—	mA

Power Supply	12V 3A DC (Recommended).				
Reliability Test					
Item	Condition	Min.	Typ.	Max.	Unit
Working Temperature	60%RH at 12V voltage	-30	25	70	℃
Storage Temperature	—	-30	25	85	℃
Working Humidity	25℃	10%	60%	90%	RH
Protection Paint	—	—	None	—	—
Interface					
Item	Condition	Min.	Typ.	Max.	Unit
Baud Rate	Standard	1200	115200	115200	bps
	User Defin	1200	—	115200	bps
Serial Mode	Serial Port*3 (2*RS232/TTL, 1*RS485).				
User Interface	Standard serial communication protocol. 4Pin_2.54mm socket.				
USB	USB DEBUG*1. USB HOST*3.				
Ethernet	Support 10m/100m Ethernet.				
Wi-Fi/Bluetooth	Support 802.11b/g/n Wi-Fi wireless network; Bluetooth is optional				
4G LTE Module	4G LTE Module/GPS. (Optional)				
Peripherals					
Microphone	Audio input interface.				
Loudspeaker	2-channel, 4Ω/3W loudspeaker.				
HDMI	HDMI output interface.				
TF card	Yes				



Interface Description



Num.	Interface Name	Description
J0	Power	12V2A power supply
J1	SPK_R	Right channel audio output interface
J2	SPK_L	Left channel audio output interface
J3	MIC	Audio input interface
J4	UART0	Device name: ttyS0. Pin definition: GND, RX, TX, 5V
J5	UART1	Device name: ttyS1. Pin definition: GND, RX, TX, 5V
J6	UART3	Device name: ttyS3. Pin definition: GND, RX, TX, 5V (only available for RK3188, choose one from J6 and J8)
J7	UART4	Device name: ttyS4. Pin definition: GND, RX, TX, 5V
J8	RS485	Pin definition: 5V, A, B, GND
J9	RJ45 interface	Support 10M/100M network
J10	Wireless Network	Support IEEE802.11b/g/n network. Support Wireless & Bluetooth 2-in-1.
J11	SIM card	Nano-SIM supported (Optional)
J12	MINI PCIE 4G	4G LTE Module/GPS (Optional)
J13	Debug interface	Not open temporarily
J14	USB_HOST1	Horizontal USB2.0 (Vertical 4P2.54mm). Support USB Peripherals
J15	USB_HOST2	Horizontal USB2.0 (Vertical 4P2.54mm). Support USB Peripherals
J16	USB_HOST3	Horizontal USB2.0 (Vertical 4P2.54mm). Support USB Peripherals
J17	USB_Micro	OTG /App debugging/ Firmware upgrade interface
J18	HDMI	HDMI output interface
J19	Buzzer	

J20	Recovery	Short-circuit to enter firmware burning mode
J21	RTC	Supply system RTC
J22	TF Card	
J23	Wake Up	
J24	User interface	Pin Definition: 12V, 12V, GND, GND, ttyS0-RX, ttyS0-TX, ttyS1-RX, ttyS1-TX





1. Location hole is used as position reference

2. Unmarked Tolerance is +/-0.3mm

Active area is marked in Dash lines

Part No.	P10768MS150C_T01				 PROCLUS PROCLUS TECHNOLOGIES INS.	
Datasheet	A4	Drawn by	Proculus	Date		
Proportion	1:1	Verified by		Date		
Unit	mm	Confirmed by		Date		